

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 212 948 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
12.06.2002 Bulletin 2002/24

(51) Int Cl.7: **A23G 9/02, A23G 9/20**

(21) Application number: **01309242.4**

(22) Date of filing: **31.10.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **06.12.2000 EP 00310834**

(71) Applicants:
• **UNILEVER PLC**
London EC4P 4BQ (GB)
Designated Contracting States:
GB IE CY
• **UNILEVER N.V.**
3013 AL Rotterdam (NL)
Designated Contracting States:
**BE CH DE DK ES FI FR GR IT LI LU MC NL PT SE
TR AT**

(72) Inventors:
• **Spindler, Suzanne Mary, Unilever R&D Colworth
Sharnbrook, Bedford MK44 1LQ (GB)**
• **Wix, Loyd, Unilever R&D Colworth
Sharnbrook, Bedford MK44 1LQ (GB)**

(74) Representative: **Hugot, Alain et al**
Unilever plc,
Patent Division,
Colworth House
Sharnbrook, Bedford MK44 1LQ (GB)

(54) **Aerated compositions, process and apparatus for achieving such aerated compositions**

(57) The present invention provides a cold extruded composition with at least 90% overrun, wherein said composition comprises a fat phase which has a high ratio of liquid fat to solid fat at the processing temperature. The present invention also relates to a process for the

production of such compositions wherein a mix is aerated in an internal volume of a freezer barrel with a aerating means which has a low displacement of said internal volume, prior to cold extrusion.

EP 1 212 948 A2

Description

Technical field of the invention

[0001] The invention relates to aerated food compositions. More particularly the invention relates to aerated ice cream compositions which comprise a fat component having a low melting point and thereby retaining liquid properties at processing temperatures. The invention further relates to a process for preparing such compositions by cold extrusion. Finally the invention relates to apparatus and the use thereof for preparing the compositions novel concerned.

Background to the invention

[0002] It is known to aerate a mix for the preparation of an ice cream through the use of an aerating means comprising a rotating element that fits into the barrel of a continuous ice cream freezer. This aerating means is commonly referred to as a dasher. On rotation the dasher imparts mechanical energy into the mix in order to achieve aeration and generate a fat network by aggregating some of the fat droplets. This aggregation is necessary for product stability.

[0003] For many industrial continuous freezers there are a variety of dasher types available. These can be differentiated from each other by the volume displaced within the freezer barrel which can be assessed by simply filling the freezer barrel with a liquid, such as water, and measuring the volume of liquid displaced when the dasher is fitted therein. A dasher described as a series 80 indicates that this rotating element occupies 80% of the available internal volume of the freezer barrel so that only 20% of the space is available to be occupied by the mix to be aerated. By contrast a series 15 dasher, also known in the art, demonstrates a displacement volume of only 15% of the internal barrel volume, the remaining 85% being available to be occupied by a mix to be aerated.

[0004] In conventional ice cream processing it is generally accepted that higher displacement dashers such as the series 80 give rise to high quality ice cream being highly churned (Ice Cream 5th Edition, W.S. Arbuckle et al., page 183) thus showing optimal levels of fat destabilisation, while at the same time product dryness, good meltdown resistance and product hardness. These displacement dashers are therefore the standard form of aerating means used in ice cream manufacture.

[0005] Cold extrusion of aerated compositions is also known in the art. US 5,345,781 describes the extrusion of a pre-aerated foam through a freezing device. Pre-aeration has conventionally been undertaken through the use of an aerating means in the form of a high displacement dasher (Ice Cream 5th Edition, W.S. Arbuckle et al., page 184). The foam once aerated is then transferred to cold extrusion apparatus. Figure 3 of US 4,345,781 illustrates this approach.

[0006] Cold extrusion allows a convenient and preferred means of preparing ice cream, however this freezing route has been found by the applicants to present additional processing problems with particular formulations that contain a high ratio of liquid to solid fat at the processing temperature. The applicants when applying the conventionally combination of an aeration means with 80% displacement and cold extrusion apparatus, have observed an inability to achieve desired levels of overrun (>90%). This loss of overrun can be so severe as to give rise to phase separation and the loss of control of the process to the extent that extrusion apparatus may become blocked.

[0007] The ice cream formulations prepared by conventional aeration and cold extrusion systems comprise a fat phase with a relatively high melting point. This means that little if any liquid fat is present at the processing temperature.

[0008] The applicants have identified a need to extend the range of fats that can be applied to ice cream manufacture. In particular there is a need for the development of novel ice cream compositions which have formulations that can comprise a fat component having a lower melting point, thus imparting a higher level of liquid fat in the fat phase at the processing temperature. At the same time formulations must maintain the high degree of stable aeration and low levels of destabilised fat and overrun loss characteristic of conventional ice creams. The ability to use increasingly varied fats would also allow the manufacture of ice cream at a reduced cost.

[0009] The technical problem to be solved by the present invention therefore relates to the production of novel ice cream formulations, wherein said formulations comprise fat types that have not been conventionally applied to commercial ice cream manufacture due to high levels of liquid fat that they impart in the fat phase of a mix at the processing temperature. More particularly the problem has been found to particularly relate to enabling the cold extrusion of these so mentioned novel ice cream formulations.

[0010] It has been surprisingly been found that a solution to this problem resides in the use of equipment which has never been used for this type of formulation before. There is no suggestion in the prior art that this type of equipment has any positive influence on the destabilisation of fat, phase separation or overrun loss during the processing of a composition.

[0011] The present invention seeks to provide a stable composition with at least 90% overrun, wherein said composition comprises a fat phase which has a high ratio of liquid fat to solid fat at the processing temperature. More particularly the present invention provides aerated novel compositions of this type which are also suitable for cold extrusion.

Tests and definitions

[0012] Levels of liquid fat can be determined

by ^{13}C -NMR spectroscopy wherein the liquid fat level of an emulsion of an ice cream mix of the invention is determined.

[0013] Measurements carried out at -5°C & $+50^\circ\text{C}$ for 100% fully liquid state. ^{13}C -NMR is carried out on a Bruker AMX-400 high resolution NMR spectrometer, with 10mm sample tubes. Data is acquired with inverse gated proton de-coupling and suitable interscan delay to ensure quantitative results. Volume of samples for 100% liquid measurement was reduced to keep total sample within probe coils and hence negate any complications due to premix separation. Measurements at -5°C is carried out after external equilibration for at least 2hrs. 100% liquid measurements is carried out after at least 30min equilibration, at $+50^\circ\text{C}$, in spectrometer probe. All temperatures verified using external thermocouple meter. Liquid fat content is determined by integration of fat signals (15-40ppm), relative to integral of sugar signals (60-85ppm). At -5°C and above the integral of sugar signals will remain constant and hence can be used as an internal standard. The proportion of liquid fat at the chosen temperature is calculated by comparison of integrals with those from fat signals from the 100% "melted" sample.

[0014] For the purpose of the invention overrun can be determined as described in Ice Cream 4th Edition, Arbuckle et al., page 181.

[0015] Cold extrusion (coldex) is used to denote a cooling system wherein a material enters extrusion apparatus a temperature which is somewhat higher than that at the point of extrusion. Typically in the cold extrusion of ice cream material enters the extrusion apparatus at about -13°C and subsequently about -18°C at the point of extrusion.

Brief description of the invention

[0016] It is a first object of the present invention to provide a cold extruded composition comprising a fat phase and having an overrun of at least 90%, characterised in that at least 45 % weight by weight of the fat phase is liquid at -5°C .

[0017] In a preferred embodiment the cold extruded composition of the invention is an ice cream.

[0018] In the light of conventional teachings that an aerating means that displaces 80% of freezer barrel volume is most suited to giving the best quality ice cream in terms of optimal fat de-emulsification, product dryness, good meltdown resistance and product hardness; it is unexpected to find that the novel compositions of the invention cannot be processed to an ice cream of acceptable quality by this route.

[0019] It has been found that the use of cold extrusion apparatus leads to an increase in destabilised fat levels in the high liquid fat compositions of the invention. This is due to the temperature of extrusion and the increased shear stress imposed on the ice cream. Similarly a high displacement aerating means will also lead to unacceptable

high levels of destabilised fat in those formulations of the invention due to the reduced residence time of the mix in the freezer barrel. The combined effect of this phenomenon occurring at both stages of processing has been found to make it impossible to prepare ice cream compositions with liquid fat levels in excess of 45 % w/w of the fat phase by using the combination of a high displacement aerating means and cold extrusion apparatus.

[0020] The presently proposed solution to this newly identified problem is to provide for the aeration of a composition as described above with a aerating means which displaces less than 40% of a freezer barrel internal volume prior to entry of said mix into cold extrusion apparatus.

[0021] It is a second object of the present invention to provide a process for the preparation of a cold extruded composition, wherein said process comprises;

- (i) aerating a mix comprising a fat phase in a freezer barrel enclosing an internal volume, said internal volume comprising an aeration means;
- (ii) extruding the mix through a cold extruding means;

characterised in that, said aeration means displaces less than 40% of said internal volume and at least 45% weight by weight of the fat phase is liquid at -5°C .

[0022] By way of the present invention a process has been devised as described above wherein a selected displacement range for the aerating means of less than 40% of the internal freezer barrel volume, has been found to yield a stable aerated ice cream demonstrating good properties. These properties include low fat de-emulsification, product dryness, good meltdown resistance and product hardness for the novel compositions provided herein.

[0023] Through the use of an aerating means that displaces less than 40% of internal freezer barrel volume it has been possible to achieve aeration levels in excess of 90% overrun for a mix having at least 45 % w/w of its fat phase in a liquid state at -5°C . In a preferred embodiment, the invention therefore comprises a process for the preparation of a cold extruded composition as disclosed above wherein said mix is aerated to an overrun of at least 90%.

[0024] It is preferred that the aerating means used for the purpose of the invention displaces at least 10% of the internal barrel volume, more preferably at least 15%, most preferably the aerating means displaces from 15 to 30% of the internal freezer barrel volume. Suitable aeration means are commercially available from the manufacturer WCB.

[0025] It is recognised that as the proportion of liquid fat in the fat phase increases it becomes more preferable to choose a aerating means towards the lower end of the displacement range specified above. This increases the residence time of the mix in the freezer bar-

rel and thereby allows a longer and more effective aeration period without destabilisation of the fat.

[0026] A composition of the invention may comprise one or more fat components derived from any fat source having a low melting point, wherein the addition of said component(s) results in a proportion of at least 45 % w/w liquid fat in the fat phase of the product at -5°C. Preferably the fat phase comprises one or more fats selected from the group comprising soy bean oil, palm oil, walnut oil, pistachio oil, hazelnut oil, hydrogenated or partially hydrogenated sunflower oil.

[0027] For a cold extruded ice cream according to the invention it is preferable that the proportion of the fat phase being liquid at -5°C is less than 55% w/w of the phase. A mix comprising a fat phase with a liquid fat in the range 45 to 55% w/w can therefore be suitably processed by the invention, most preferably 47 to 53% w/w of the fat phase is liquid at -5°C.

[0028] The total fat content may range from 3% w/w to 15% w/w of the composition, preferably 5 to 10% w/w. Most preferred fat content of a composition according to the invention is about 8% w/w of the composition.

[0029] Preferably compositions of the invention have an overrun of at least 100%, more preferably the level of overrun is at least 110%.

[0030] It is a third object of the invention to provide an apparatus comprising a freezer barrel enclosing an internal volume comprising an aerating means, said freezer barrel further comprising an outflow means allowing passage of aerated material to a cold extruder, characterised in that said aerating means displaces less than 40% of the internal volume of said freezer barrel. Preferably the outflow means is continuous with the cold extruder.

[0031] The cold extrusion apparatus used in the process of the invention may comprise either a single or twin screw extruder. Preferably the extruder is the single screw type.

[0032] A fourth object of the invention provides for the use of the apparatus as described above in the preparation of a cold extruded ice cream, wherein preferably said ice cream has a formulation in accordance with the invention.

Detailed Description

Example

[0033] 500 kg of an ice cream mix A was prepared with the composition indicated in table 1. The mix was made in a large scale mix plant at a temperature of approximately 65-70°C, wherein the order of ingredients into the tank was water, skimmed milk powder, sugars and stabilisers/emulsifier compounds (suitably Cremodan™ SE 019 available from Danisco™ ingredients) and fats/oils. MD40 is a refined and spray dried glucose syrup in powder form having 40% dextrose equivalent and is sold as Cerestar™ or Morsweet™. The mix was

homogenised at $1.379 \times 10^7 \text{ Nm}^{-2}$ - 138 Bar (2000psi) and then pasteurised at 83°C for 15 seconds. Following pasteurisation the mixture was immediately chilled to approximately 4°C and aged in a ageing tank for at least 2 hours.

[0034] According to the methodology described above the level of liquid fat at the processing temperature of -5°C was 53 % w/w of the fat phase in the product.

Table 1:

Mix A	
Ingredient	Parts by weight
Sucrose	13.61
Walnut oil	2.86
Skimmed milk powder	10.08
MD40	4.05
Butter fat	5.14
Cremodan SE 019	0.45
Water	63.81

[0035] Mixes prepared as described and according to the above formulation were separately processed through freezer barrels comprising an aerating means of 15, 30 and 80% displacement of the internal volume of the barrel.

[0036] The aerated material from the freezer barrel was then passed through a conventional single screw extruder (SSE). Inlet pressure to the SSE was maintained constant at $7 \times 10^5 \text{ Nm}^{-2}$ (7 bar) and the aerated composition in the SSE remained at a temperature between -12 and -15°C.

[0037] The effect of varying the displacement of the aerating means on the extruded product was assessed, wherein it was observed that an aerating means of 15 or 30% displacement it was possible to achieve a cold extruded product having an overrun of at least 90% wherein said product demonstrated good organoleptic properties showing a creamy texture with little or no ice and no phase separation or unacceptable level of fat destabilisation.

[0038] In contrast where an aerating means having a displacement of 80% was used with this formulation the extruded product showed destabilisation of fat, phase separation and overrun loss. This product was highly inferior to that obtained with an aerating means of 15 or 30% displacement.

Claims

1. A cold extruded composition comprising a fat phase and having an overrun of at least 90%, **characterised in that** at least 45%w/w of the fat phase is liquid at -5°C.
2. A composition according to claim 1 wherein said

composition is an ice cream.

3. A process for the preparation of a cold extruded composition, wherein said process comprises;

5

(i) aerating a mix comprising a fat phase in a freezer barrel enclosing an internal volume, said internal volume comprising an aeration means;

(ii) extruding the mix through a cold extruding means;

10

characterised in that, said aeration means displaces less than 40% of said internal volume and at least 45% w/w of the fat phase is liquid at -5°C.

15

4. A process according to claim 3, wherein said mix is aerated to an overrun of at least 90%.

5. A process according to either claim 3 or 4 wherein said composition is an ice cream.

20

6. Apparatus comprising a freezer barrel enclosing an internal volume comprising an aerating means, said freezer barrel further comprising an outflow means allowing flow of aerated material into a cold extruder, **characterised in that** said aerating means displaces less than 40% of the internal volume of said freezer barrel.

25

30

7. Use of an apparatus according to claim 6 in the preparation of a cold extruded ice cream according to claim 1.

35

40

45

50

55



(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
02.01.2004 Bulletin 2004/01

(51) Int Cl.7: **A23G 9/02**, A23G 9/20,
A23G 9/22, A23P 1/16,
A23L 1/19, A23G 9/28

(43) Date of publication A2:
12.06.2002 Bulletin 2002/24

(21) Application number: **01309242.4**

(22) Date of filing: **31.10.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Spindler, Suzanne Mary, Unilever R&D Colworth**
Sharnbrook, Bedford MK44 1LQ (GB)
• **Wix, Loyd, Unilever R&D Colworth**
Sharnbrook, Bedford MK44 1LQ (GB)

(30) Priority: **06.12.2000 EP 00310834**

(74) Representative: **Hugot, Alain et al**
Unilever plc,
Patent Division,
Colworth House
Sharnbrook, Bedford MK44 1LQ (GB)

(71) Applicants:
• **UNILEVER PLC**
London EC4P 4BQ (GB)
Designated Contracting States:
CY GB IE
• **UNILEVER N.V.**
3013 AL Rotterdam (NL)
Designated Contracting States:
AT BE CH DE DK ES FI FR GR IT LI LU MC NL PT
SE TR

(54) **Aerated compositions, process and apparatus for achieving such aerated compositions**

(57) The present invention provides a cold extruded composition with at least 90% overrun, wherein said composition comprises a fat phase which has a high ratio of liquid fat to solid fat at the processing temperature. The present invention also relates to a process for the

production of such compositions wherein a mix is aerated in an internal volume of a freezer barrel with a aerating means which has a low displacement of said internal volume, prior to cold extrusion.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 01 30 9242

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 400 406 A (MORLEY ROBERT G ET AL) 23 August 1983 (1983-08-23) * column 5, line 36 - line 49; example 6 * * column 4, line 41 - line 60 * * column 1, line 22 - line 43; claims 1,6,14,15 * * column 9, line 29 - line 60 * ---	1-7	A23G9/02 A23G9/20 A23G9/22 A23P1/16 A23L1/19 A23G9/28
X	GB 2 019 187 A (UNILEVER LTD) 31 October 1979 (1979-10-31)	1-5	
Y	* claims 1-8; figures * ---	6,7	
X	US 5 919 510 A (FAYARD GILLES ET AL) 6 July 1999 (1999-07-06) * claim 3; figures * ---	6,7	
X	FR 2 745 153 A (RIVEIRE SILVENTE ET ASSOCIES R) 29 August 1997 (1997-08-29)	1,2,6,7	
Y	* page 2, line 27 - page 3, line 18 * * page 7, line 13 - line 17 * * page 9, line 24 - line 26 * * page 10, line 3,4 * * page 10, line 11 - line 16; claims 1,4,9,15,18,19 * ---	3-5	TECHNICAL FIELDS SEARCHED (Int.Cl.7) A23G A23P A23L
Y	US 4 162 127 A (HEILIGER LEONARD R ET AL) 24 July 1979 (1979-07-24) * column 3, line 2 - line 6; figures 1,8,9 * * column 4, line 6 - line 10 * ---	3-5	
Y	EP 0 191 487 A (TOYO JOZO KK) 20 August 1986 (1986-08-20) * page 7, line 9 - line 16; claims 1,5-7; examples 1,2 * * page 8, line 11 - line 14 * ---	1-7	
		-/--	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 October 2003	Examiner Guyon, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 9242

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	GB 371 406 A (FREDERICK LYSTER GOLDBY) 18 April 1932 (1932-04-18) * page 2, line 115 - line 120; claims; figures *	1-7	
X	EP 0 559 316 A (MORINAGA MILK INDUSTRY CO LTD) 8 September 1993 (1993-09-08) * page 5, line 23 - page 6, line 13 * * column 7, paragraph 1; claims 1,4,7,8; figures; examples 1,4,5,8,11 *	1,2,6,7	
Y	DE 89 08 631 U (SPADOTTO C.) 23 November 1989 (1989-11-23) * claim 1; figures 1,3,4 *	3-5	
Y	US 4 798 734 A (KANEDA KICHIZO) 17 January 1989 (1989-01-17) * column 5, line 17 - line 65 * * column 7, line 7 - line 28; claims 1,2; examples * * column 8, line 46 - line 53 * * column 8, line 9 - line 24 *	3,5	
X	GB 538 187 A (CHERRY BURRELL CORP) 24 July 1941 (1941-07-24) * the whole document *	1,2	
Y	US 4 421 778 A (KAHN MARVIN L ET AL) 20 December 1983 (1983-12-20) * column 6, line 31 - line 49; examples 1,3 *	3-7	
Y	WO 00 70961 A (SPECIALITY EQUIP CO ;BOYER GEORGE C (US); DUNCAN DAVID C (US)) 30 November 2000 (2000-11-30) * figures 6A,10,14A *	3-7	
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		30 October 2003	Guyon, R
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (03.02.92) (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 9242

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 6 082 120 A (ROGGE FRIEDRICH H F ET AL) 4 July 2000 (2000-07-04) * claims; figures * -----	1,6,7	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 October 2003	Examiner Guyon, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 9242

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-10-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 4400406	A	23-08-1983	US	4346120 A	24-08-1982
			US	4400405 A	23-08-1983
			US	4427701 A	24-01-1984

GB 2019187	A	31-10-1979	AT	375817 B	10-09-1984
			AT	306879 A	15-02-1984
			AU	532829 B2	13-10-1983
			AU	4640979 A	01-11-1979
			BE	875826 A1	24-10-1979
			CA	1117355 A1	02-02-1982
			CH	652567 A5	29-11-1985
			DE	2916395 A1	31-10-1979
			DK	166879 A	25-10-1979
			ES	479892 A1	16-08-1980
			FR	2423986 A1	23-11-1979
			IE	48114 B1	03-10-1984
			IT	1118967 B	03-03-1986
			LU	81186 A1	07-11-1979
			NL	7903236 A	26-10-1979
			PT	69543 A	01-05-1979
			SE	7903559 A	25-10-1979
			US	4219581 A	26-08-1980
			ZA	7901935 A	26-11-1980

US 5919510	A	06-07-1999	AT	177909 T	15-04-1999
			AU	1471999 A	15-04-1999
			AU	703449 B2	25-03-1999
			AU	3770095 A	30-05-1996
			BR	9505269 A	21-10-1997
			CA	2163284 A1	24-05-1996
			CN	1132595 A ,B	09-10-1996
			CZ	9503076 A3	17-07-1996
			DE	69508529 D1	29-04-1999
			DE	69508529 T2	09-09-1999
			DK	713650 T3	11-10-1999
			EG	20619 A	30-09-1999
			EP	0713650 A1	29-05-1996
			ES	2130520 T3	01-07-1999
			FI	955594 A	24-05-1996
			GR	3030143 T3	31-08-1999
			HU	74491 A2	28-01-1997
			JP	8205783 A	13-08-1996
			KR	244784 B1	02-03-2000
			NO	954687 A	24-05-1996
			NZ	280507 A	26-01-1998
			PL	311434 A1	27-05-1996

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 9242

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-10-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5919510	A		RU 2154950 C2	27-08-2000
			SG 35034 A1	01-02-1997
			SK 144495 A3	05-06-1996
			TR 960494 A2	21-07-1996
			ZA 9509682 A	14-05-1997
FR 2745153	A	29-08-1997	FR 2745153 A1	29-08-1997
			AT 200609 T	15-05-2001
			AU 1928897 A	10-09-1997
			CA 2247097 A1	28-08-1997
			CN 1211900 A ,B	24-03-1999
			DE 69704610 D1	23-05-2001
			DE 69704610 T2	06-12-2001
			DK 878998 T3	13-08-2001
			EP 0878998 A1	25-11-1998
			ES 2159112 T3	16-09-2001
			WO 9730600 A1	28-08-1997
			GR 3036236 T3	31-10-2001
			JP 2000506004 T	23-05-2000
			NO 983895 A	23-10-1998
			PT 878998 T	30-10-2001
			US 6558729 B1	06-05-2003
US 4162127	A	24-07-1979	NONE	
EP 0191487	A	20-08-1986	JP 61185155 A	18-08-1986
			EP 0191487 A2	20-08-1986
GB 371406	A	18-04-1932	NONE	
EP 0559316	A	08-09-1993	JP 2846537 B2	13-01-1999
			JP 5328905 A	14-12-1993
			CA 2087648 A1	23-07-1993
			DE 69324398 D1	20-05-1999
			DE 69324398 T2	04-11-1999
			DE 559316 T1	24-02-1994
			EP 0559316 A1	08-09-1993
			JP 3090264 B2	18-09-2000
			JP 11123051 A	11-05-1999
			JP 2956897 B2	04-10-1999
			JP 11123049 A	11-05-1999
			JP 2001000114 A	09-01-2001
			US 5403611 A	04-04-1995
DE 8908631	U	12-10-1989	DE 3905946 A1	30-08-1990
			DE 8908631 U1	12-10-1989

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 9242

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-10-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 4798734	A	17-01-1989	JP	1499610 C	29-05-1989
			JP	61031056 A	13-02-1986
			JP	63044346 B	05-09-1988
			CA	1237327 A1	31-05-1988
			DE	3521083 A1	30-01-1986
			FR	2568105 A1	31-01-1986
			GB	2162039 A ,B	29-01-1986
			IT	1183579 B	22-10-1987
			KR	8902394 B1	03-07-1989

GB 538187	A	24-07-1941	NONE		

US 4421778	A	20-12-1983	CA	1265379 A1	06-02-1990
			CA	1272634 A2	14-08-1990
			JP	1777193 C	28-07-1993
			JP	4058302 B	17-09-1992
			JP	59088047 A	21-05-1984
			JP	5168415 A	02-07-1993
			JP	2609021 B2	14-05-1997
			JP	5068485 A	23-03-1993
			JP	2509403 B2	19-06-1996
			JP	5068486 A	23-03-1993
			US	4853243 A	01-08-1989
			US	4552773 A	12-11-1985

WO 0070961	A	30-11-2000	AU	4858900 A	12-12-2000
			AU	5031700 A	12-12-2000
			AU	5144900 A	12-12-2000
			AU	5280500 A	12-12-2000
			AU	5867400 A	12-12-2000
			EP	1178734 A1	13-02-2002
			EP	1179168 A1	13-02-2002
			EP	1178735 A1	13-02-2002
			JP	2003500034 T	07-01-2003
			JP	2003505011 T	12-02-2003
			JP	2003521884 T	22-07-2003
			WO	0071959 A1	30-11-2000
			WO	0070961 A1	30-11-2000
			WO	0071946 A2	30-11-2000
			WO	0070962 A1	30-11-2000
			WO	0070963 A1	30-11-2000
			US	6553779 B1	29-04-2003
			US	6494055 B1	17-12-2002
			US	6490872 B1	10-12-2002

US 6082120	A	04-07-2000	DE	3918268 C1	26-07-1990

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 9242

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-10-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6082120 A		AT 116528 T	15-01-1995
		AU 5670190 A	07-01-1991
		DD 294856 A5	17-10-1991
		WO 9014775 A1	13-12-1990
		DK 401512 T3	28-08-1995
		EP 0401512 A1	12-12-1990
		ES 2066900 T3	16-03-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82